

XL PERFORMANCE

ALL IN! ONE.

FAST FLEXIBLES. RELIABLE RIGIDS

Colorado XL-series

UVgel 3.4m graphics production printer

Canon



COLORADO XL-SERIES

Meet the Colorado XL-series. It's a 3.4m graphics production printer for fast flexibles and reliable rigids. It handles everything from unattended printing of posters, banners and soft signage to high-speed production of displays, packaging, interior décor and more.

The Colorado XL-series is based on our unique UVgel technology, introduced to the market in 2017 with the launch of the 1.6m Colorado roll-to-roll printer. UVgel produces robust, lightfast, scratch-resistant prints with a spectacular colour gamut. Today, thousands of large-format graphics print service providers and print factories around the world benefit from the image quality and creative effects that are only possible by jetting UVgel.

The Colorado XL-series: wider¹, faster¹ and ready for rigids¹

The Colorado XL-series brings you all the advantages of UVgel technology, now even wider and faster, with one gel set for both rigid and roll-to-roll printing up to a comfortable 3.4 metres.

With the FLXfinish⁺ option

Produce eye-catching applications with the option to print matte, gloss or a combination² of both within a single print without the need for varnish.

With the UVgel White option

Effortlessly overcome the common challenges associated with white ink. Print white like any other colour, even for multilayer modes, and use considerably less gel.

With the FLXture option

Add subtle surface detail to your prints to create a luxurious feel.

A modular design to choose what you use

The Colorado XL-series is available in a roll-to-roll, hybrid and dual-roll version with varying media handling options.

A future-proof concept

Choose the configuration that fits your current business needs and upgrade your printer later when your business demands are growing.

A design to support your sustainability efforts

Thanks to UVgel, you can produce with low-temperature curing, low gel consumption, odourless operation and smart automation that promotes first-time-right printing to help minimise waste.

A smart investment

The Colorado XL-series is designed to bring outstanding Total Cost of Ownership and Return on Investment to your large-format graphics business.



¹ Compared to the Colorado M-series
² Available with R1.1

Colorado XL-series

Technical specifications

Metric



Printing		
Printing method	UVgel piezoelectric inkjet	UVgel piezoelectric inkjet
PRINTING MODES: GLOSS	●	●
Gloss Express	211 m²/hour	211 m²/hour
Gloss Speed	141 m²/hour	141 m²/hour
Gloss Production	106 m²/hour	106 m²/hour
Gloss Quality	70 m²/hour	70 m²/hour
Gloss Specialty	53 m²/hour	53 m²/hour
PRINTING MODES: MATTE	○	○
Matte Speed	141 m²/hour	141 m²/hour
Matte Production	106 m²/hour	106 m²/hour
Matte Quality	70 m²/hour	70 m²/hour
Matte Specialty	53 m²/hour	53 m²/hour
Backlit	53 m²/hour	53 m²/hour
Backlit Density	30 m²/hour	30 m²/hour
PRINTING MODES: MIXED MATTE/GLOSS	○	○
FLXfinish ⁺ Quality ¹	26 m²/hour	26 m²/hour
FLXfinish ⁺ Specialty ¹	21 m²/hour	21 m²/hour
PRINTING MODES: SPOT WHITE 1 LAYER	○	○
Spot White Speed	141 m²/hour	141 m²/hour
Spot White Production	106 m²/hour	106 m²/hour
Spot White Quality	70 m²/hour	70 m²/hour
Spot White Specialty	53 m²/hour	53 m²/hour
PRINTING MODES: 2 LAYERS	○	○
White Underflood Speed	70 m²/hour	70 m²/hour
White Underflood Production	53 m²/hour	53 m²/hour
White Underflood Quality	35 m²/hour	35 m²/hour
White Underflood Specialty	27 m²/hour	27 m²/hour
White Overflood Speed	70 m²/hour	70 m²/hour
White Overflood Production	53 m²/hour	53 m²/hour
White Overflood Quality	35 m²/hour	35 m²/hour
White Overflood Specialty	27 m²/hour	27 m²/hour
PRINTING MODES: WHITE 3 LAYERS	○	○
White 3 Layers High Quality	23 m²/hour	23 m²/hour
White 3 Layers Specialty	18 m²/hour	18 m²/hour
PRINTING MODES: WHITE 5 LAYERS	○	○
White 5 Layers Quality	14 m²/hour	14 m²/hour
White 5 Layers Specialty	11 m²/hour	11 m²/hour
INK SYSTEM		
UVgel type	UVgel 860	UVgel 860
UVgel colour CMYK	●	●
UVgel White	○	○
UVGEL PACKAGING		
UVgel 860 box 2 litre	●	●
UVgel reservoir per colour	7 litre	7 litre
Refill while printing	●	●
Printhead technology		
UVgel 850 printheads CMYK	2	2
UVgel 850 printheads CMYKW	3	3
Maximum print resolution	1,800 dpi	1,800 dpi
Nozzles per printhead	4,544	4,544
High frequency drop-on-demand piezoelectric printhead	●	●
UVGEL DYNAMIC MOTION CONTROL		
Compensates for media alignment variances	●	●
PAINT		
Piezo Acoustic Integrated Nozzle Technology	●	●
Automatic maintenance	●	●



XL7 roll-to-roll

UV LED



XL7 hybrid

UV LED

Curing technology

UVGEL FULLBEAM CURING

Uniform and fast UV LED curing in one go with full width curing technology including a smart mirror system for optimised multilayer curing

PIN CURING

The system has 2 UV LED pin cure lamps attached to the printhead carriage for velvety matte effect and mixed matte/gloss FLXfinish[®] effect¹

Media

MEDIA TRANSPORT

UVGEL TRIDRIVE

UVgel TRIdrive vacuum belt system

RIGID TABLES

The optional input and output rigid tables are optimised for ergonomic rigid feeding

Input and output rigid tables, can be extended to the following sizes

MEDIA INPUT

Machine vision technology to capture media location and size

EDGEFORWARD

ROLL MEDIA

Maximum roll width

Maximum roll weight

Maximum roll diameter

Double-sided printing

Manual and semi-automatic media loading
Automatic alignment, automatic take up assistant

Media take-up system

Number of input rolls

Dual Roll¹, 2 rolls side by side, individually tensioned

Dual Roll¹ maximum width

Dual Roll¹ maximum weight

RIGID MEDIA

Minimum media width

Maximum media width

Maximum media weight

Maximum media thickness

Maximum number of lanes

Lane Assist

Gel technology

UVGEL TECHNOLOGY

Instant pinning and dotgain control

UVgel 860 suitable for roll-to-roll and rigid applications

LOW TEMPERATURE CURING

Suitable for thin and heat-sensitive media

Outstanding scratch resistance

Easy lamination, smooth ink film

High precision colour matching and consistency

Odourless and instant dry printout

FLXFINISH[®]

Choose the right finishing option for your applications: velvety matte, vibrant gloss or both combined¹ in one print

FLXTURE, AVAILABLE WITH WHITE

Textured printing with layered UVgel ink



Certifications⁷

MEDIA WARRANTY		
3M MCS warranty	●	●
Avery Dennison ICS Performance Guarantee	●	●
Mactac media warranty	●	●
ENVIRONMENTAL AND SAFE USE		
EN15102, M1, Émissions dans l'air intérieur A+	●	●
Type II ASTM F793	●	●
GreenGuard Gold	●	●
Interface		
Network connection	Ethernet (100/1,000 Mbit/s)	Ethernet (100/1,000 Mbit/s)
Dimensions and weight		
Printer W x D x H	6,090 mm x 1,450 mm x 1,700 mm	6,090 mm x 1,450 mm x 1,700 mm
Minimal operational footprint XL7 W x D	8,100 mm x 5,000 mm	8,100 mm x 7,500 mm
Printer weight (approximately)	2,000 kg	2,000 kg
Working environment		
Temperature	18 -30 °C	18 -30 °C
Humidity	20%-80%	20%-80%
Atmospheric pressure	850-1,050 mbar	850-1,050 mbar
POWER		
Ready	1.6 kW	1.6 kW
Peak	10.8 kW	10.8 kW
Input voltage	3 phase with neutral (Y) or without neutral (Δ): 220/380V	3 phase with neutral (Y) or without neutral (Δ): 220/380V
Frequency	50/60 Hz	50/60 Hz
Source	Printer is declared under Radio Equipment Directive (RED) - 2014/53/EU	Printer is declared under Radio Equipment Directive (RED) - 2014/53/EU
Regulatory certifications⁷		
Declaration of conformity	2006/42/EC (Machinery), 2014/30/EU (EMC), 2011/65/EU (RoHS)	2006/42/EC (Machinery), 2014/30/EU (EMC), 2011/65/EU (RoHS)
Safety	Printer is declared under: Machinery Directive (MD) - 2006/42/EC UL775 and CSA 22.2 no 68 Compliant with EN55011 (Class A), FCC Part 15, EN61000-6-2, EN61000-6-4	Printer is declared under: Machinery Directive (MD) - 2006/42/EC UL775 and CSA 22.2 no 68 Compliant with EN55011 (Class A), FCC Part 15, EN61000-6-2, EN61000-6-4
EMC		
Environmental	WEEE, RoHS directive 2011/65/EU, REACH, CE	WEEE, RoHS directive 2011/65/EU, REACH, CE
EMBEDDED SOFTWARE/FIRMWARE		
Colorado XL user interface	●	●
Colorado XL user interface remote	●	●
Software		
PRISMA XL SUITE		
PRISMAguide XL	○	○
PRISMAservice	●	●
Factory supported RIPs	ONYX Graphics, Caldera ¹	ONYX Graphics, Caldera ¹
Supported RIPs ⁶	PrintFactory, SAI, Fiery, ColorGATE, ErgoSoft, Shiraz, AGFA Asanti	PrintFactory, SAI, Fiery, ColorGATE, ErgoSoft, Shiraz, AGFA Asanti
API	Colorado XL-series API for third party vendors	Colorado XL-series API for third party vendors
Warranty & Service		
MANUFACTURER'S WARRANTY		
Printer: 2 years	●	●
UVgel 850 printhead: 2 years or 50,000 sqm whichever comes first ⁴	●	●
SERVICE PROGRAMME		
proCARE* (3, 4 or 5 years) ⁵	○	○

¹ Available from R1.1

² In case media edge guards are used, the print margin is 10 mm

³ Please be aware that there might be regional distinctions in

Warranty programmes, Terms and Conditions applicable

⁴ Repair or replacement of an item does not extend the warranty period of the item repaired or replaced

⁵ proCARE* including printheads

⁶ Depending on third party support

⁷ In process of certification

© 2025 Canon Production Printing

No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market.

Canon and Canon product and service names are the trademarks or registered trademarks of Canon, Inc. or Canon Production Printing Netherlands B.V. All other product and company names are trademarks or registered trademarks and are the property of their owners and are respectfully acknowledged.

Canon

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English Edition
© Canon Europa N.V., 2025